

FLOTATION TR 675

| | |
|---------------------------|--|
| TYRE SIZE | 550/60 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 154 A8/150 B |
| LI/SS FREE ROLLING | 167 A8/163 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94019816 | RC (IN) | 143.3 |
| SW (IN) | 21.7 | RIM REC | AG 16.00 |
| OD (IN) | 49.6 | ECE | E11-106R-004397 |
| SLR (IN) | 21.5 | PR | 16 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 35 | 38 | 41 |
|--------------|-------|-------|-------|
| 5 FR | 15370 | 16110 | 16820 |
| 10 FR | 13830 | 14490 | 15130 |
| 20 FR | 12300 | 12890 | 13460 |
| 25 FR | 10980 | 11510 | 12010 |
| 30 FR | 9880 | 10360 | 10750 |
| 5 DW | 10570 | 11080 | 11570 |
| 10 DW | 9510 | 9980 | 10420 |
| 20 DW | 8450 | 8860 | 9260 |
| 25 DW | 7550 | 7910 | 8270 |
| 30 DW | 6800 | 7120 | 7390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.