


FL 635

| | |
|---------------------|--|
| TIRE SIZE | 650/55 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BALPRESS / SKÖRDEMASKIN |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 167 D |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 645 | RIM REC | AG 20.00 |
| OD (MM) | 1287 | ECE | E4-106R-000803 |
| SLR (MM) | 568 | SRI | 600 |
| RC (MM) | 3901 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1590 | 1815 | 2035 | 2530 | 2880 | 3325 | 3770 | 4120 | 4515 | 4960 |
| 65 | 1745 | 1990 | 2235 | 2780 | 3165 | 3655 | 4145 | 4525 | 4960 | 5450 |
| 50 | 2115 | 2410 | 2705 | 3365 | 3830 | 4420 | 5015 | 5475 | 6005 | 6595 |
| 40 | 2375 | 2710 | 3045 | 3785 | 4305 | 4970 | 5640 | 6155 | 6750 | 7415 |
| 25 | 2760 | 3150 | 3535 | 4395 | 5000 | 5775 | 6550 | 7155 | 7840 | 8615 |
| 10 | 3140 | 3585 | 4025 | 5005 | 5690 | 6575 | 7460 | 8145 | 8930 | 9810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.