


# AGRIMAX RT 855

**250/85 R 20**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	116 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94027460	<b>RC (IN)</b>	110.7
<b>SW (IN)</b>	9.8	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	37.0	<b>RIM ALT</b>	W 7; W 9
<b>SLR (IN)</b>	16.7	<b>ECE</b>	E4-106R-000639

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1300	1490	1710	1930	2150	2370	2570	2760
25	1300	1490	1710	1930	2150	2370	2570	2760
20	1390	1600	1840	2070	2310	2550	2760	2950
5 LT	1740	2000	2290	2590	2890	3190	3440	3690
5 HT	1390	1600	1840	2070	2310	2550	2760	2950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.