


# TF 9090

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>7.50 - 18</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR / TRAILER  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 113 A6   |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 207  | <b>RIM REC</b>  | 5.50 F          |
| <b>OD (MM)</b>  | 860  | <b>ECE</b>      | E11-106R-004654 |
| <b>SLR (MM)</b> | 404  | <b>PR</b>       | 10              |
| <b>RC (MM)</b>  | 2562 | <b>TRA CODE</b> | F2              |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.75</b> |
| 30                | 1150        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.