


# RIDEMAX FL 693 M



<b>TYRE SIZE</b>	425/55 R 17
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKER / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	129 D ; 140 A8

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	420	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	894	<b>ECE</b>	E11-106R-005104
<b>SLR (MM)</b>	397	<b>SRI</b>	425
<b>RC (MM)</b>	2704		

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	595	760	945	1075	1240	1410	1540	1685	1850
50	720	920	1145	1300	1505	1705	1860	2040	2240
40	800	1025	1275	1450	1675	1900	2075	2275	2500
30	895	1150	1430	1625	1875	2125	2320	2545	2795
25	940	1200	1495	1700	1960	2225	2430	2665	2925
10	1070	1370	1700	1935	2235	2535	2765	3035	3330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.