


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / MAȘINI DE IMPLEMENTARE / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94063109	<b>RC (IN)</b>	188.5
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	62.2	<b>RIM ALT</b>	W 14 L ; W 16 L
<b>SLR (IN)</b>	28.7	<b>ECE</b>	E11-106R-005834

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
<b>40</b>	3340	3940	4530	5050	5640	6150	6760	7260	7950	8540
<b>30</b>	3510	4130	4760	5300	5930	6470	7100	7630	8360	8970
<b>25</b>	3660	4310	4960	5520	6180	6750	7400	7960	8710	9360
<b>20</b>	3840	4530	5210	5810	6490	7090	7770	8370	9150	9830
<b>5 LT</b>	4480	5270	6070	6770	7560	8260	9050	9740	10660	11450
<b>5 HT</b>	3840	4530	5210	5810	6490	7090	7770	8370	9150	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.