

AW 715

TIRE SIZE	500/50 R 17
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	149 D



РАЗМЕРЫ IS STANDARD

SW (MM)	503	RIM REC	16.00
OD (MM)	940	ECE	E11-106R-0011505
SLR (MM)	433	SRI	450
RC (MM)	2890		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
65	1075	1205	1465	1660	1920	2180	2405	2635	2895	3250
50	1305	1460	1775	2010	2325	2640	2915	3190	3505	3935
40	1465	1640	1990	2255	2610	2965	3275	3585	3935	4420
25	1695	1900	2315	2620	3030	3445	3800	4160	4575	5135
10	1935	2165	2635	2985	3455	3920	4330	4740	5210	5850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.