


# AT 621

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ЭКСКАВАТОР-ПОГРУЗЧИК / ЭКСКАВАТОР-ПОГРУЗЧИК / ПОГРУЗЧИК
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	129 A8
<b>LI/SS FREE ROLLING</b>	142 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	308	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	987	<b>RIM ALT</b>	11.0
<b>SLR (MM)</b>	434	<b>ECE</b>	E11-106R-005329
<b>RC (MM)</b>	2916	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650
10 DW	2590
25 DW	2200
30 DW	2070
40 DW	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.