

AGRIMAX RT 657

TIRE SIZE	600/65 R 30
UM	US STANDARD
MACHINERY	VENDEMMIATRICE / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	155 D ; 158 A8



DIMENSIONI US STANDARD

CODICE USA	94032310	RIM REC	DW 20 B
SW (IN)	24.1	RIM ALT	W 18 L
OD (IN)	60.7	ECE	E4-106R-001825
SLR (IN)	27.4	TRA CODE	R1W
RC (IN)	181.5	TREAD DEPTH (32nd)	68.67

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4100	4780	5390	5990	6580	7100	7860	8540
30	4310	5030	5650	6280	6910	7450	8260	8970
25	4500	5250	5910	6560	7220	7780	8620	9370
20	4730	5510	6190	6890	7570	8170	9050	9830
5 LT	5500	6420	7220	8020	8830	9510	10540	11450
5 HT	4730	5510	6190	6890	7570	8170	9050	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.