

AGRIMAX V- FLECTO

VF 520/85 R 50

UM IS STANDARD

CONSTRUCTION  RADIAL

VERSION STEEL BELTED

TIRE TYPE TL

177 D



UNDEFINED IS STANDARD

SW (MM)	535	RIM REC	DW 18 L
OD (MM)	2160	RIM ALT	DW 16 L
SLR (MM)	972	ECE	E11-106R-0011305
RC (MM)	6493	SRI	1025

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3120	3585	4115	4645	5175	5710	6240	6640
FROM 65 TO 40	3430	3940	4525	5110	5690	6275	6860	7300
30	3495	4020	4615	5210	5805	6400	6995	7445
20	3565	4095	4705	5310	5920	6525	7130	7590
10	3770	4335	4975	5620	6260	6905	7545	8030
UPTO 10 CYC WIT H FRONT LOADER	4805	5520	6340	7155	7975	8790	9610	10220
10 HT	3495	4020	4615	5210	5805	6400	6995	7445

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.