


# AGRIMAX TERIS

<b>TIRE SIZE</b>	520/85 R 42
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOISSONNEUSE / MACHINE À RÉCOLTER LE COTON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1951	<b>RIM ALT</b>	W15L; DW15L; DD16L; W16L; DD18L; DW18L; W18L
<b>SLR (MM)</b>	890	<b>ECE</b>	E4-106R-001829
<b>RC (MM)</b>	5851	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.8
65	1850	2185	2520	2800	3140	3420	3980	4540	5100	5600	-
50	1945	2295	2650	2940	3295	3590	4175	4765	5355	5880	-
40	2025	2395	2765	3070	3440	3745	4360	4970	5585	6135	-
30	2130	2515	2900	3220	3610	3930	4575	5250	5865	6440	-
25	2195	2590	2990	3320	3720	4055	4715	5380	6045	6640	-
10	2775	3280	3780	4200	4705	5125	5965	6805	7645	8400	-
10 CYC*	-	-	-	-	-	-	-	-	-	-	9520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.