


FL 630 ULTRA

| | |
|---------------------|--|
| TIRE SIZE | 500/60 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ESPALHADOR / CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D ; 166 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|---------------------|
| CÓDIGO USA | 94046065 | RC (IN) | 141.4 |
| SW (IN) | 19.8 | RIM REC | AG 16.00 |
| OD (IN) | 46.1 | RIM ALT | 15.00; 16.00; 17.00 |
| SLR (IN) | 20.5 | ECE | E4-106R-001404 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 45 | 2490 | 2890 | 3270 | 3920 | 4600 | 5260 | 5890 | 6550 | 7160 | 7780 |
| 40 | 2730 | 3160 | 3590 | 4300 | 5050 | 5750 | 6460 | 7180 | 7860 | 7540 |
| 30 | 3320 | 3840 | 4340 | 5170 | 6110 | 6970 | 7800 | 8690 | 9510 | 10340 |
| 25 | 3750 | 4330 | 4920 | 5910 | 6860 | 7850 | 8800 | 9790 | 10760 | 11680 |
| 15 | 4320 | 5000 | 5680 | 6790 | 7970 | 9060 | 10210 | 11310 | 12420 | 13500 |
| 5 | 4930 | 5700 | 6460 | 7720 | 9040 | 10360 | 11570 | 12900 | 14150 | 15380 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.