

# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>325/70 R 18 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / ТЕХНИКА ДЛЯ ВНЕСЕНИЯ УДОБРЕНИЙ / УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	132 G



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	322	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	916	<b>ECE</b>	E11-54R-0020959
<b>SLR (MM)</b>	410		
<b>RC (MM)</b>	2771		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.5	3.0	3.5
90	1095	1285	1530	1770	2000
65	1180	1390	1650	1915	2160
40	1255	1480	1760	2040	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.