


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 900/60 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	189 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	900	<b>RIM REC</b>	DW 30B
<b>OD (MM)</b>	2142	<b>ECE</b>	E11-106R-006165
<b>SLR (MM)</b>	937	<b>SRI</b>	1025
<b>RC (MM)</b>	6390		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	4590	5340	6180	6930	7680	8435	9370
FROM 65 TO 40	5045	5870	6795	7620	8445	9270	10300
30	5145	5985	6930	7770	8610	9455	10505
20	5245	6100	7065	7920	8780	9640	10710
10	5545	6455	7470	8380	9285	10195	11330
*UPTO 10 CYC WITH FRONT LOADER	7060	8215	9510	10665	11820	12975	14420
10 HT	5145	5985	6930	7770	8610	9455	10505

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.