


MULTIMAX MP 522



| | |
|---------------------|--|
| TYRE SIZE | 540/70 R 24 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 168 A8/B |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94052264 | RC (IN) | 162.7 |
| SW (IN) | 20.9 | RIM REC | DW 16 L |
| OD (IN) | 53.8 | RIM ALT | DW 18 L |
| SLR (IN) | 24.1 | ECE | E11-106R-002967 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5930 | 7040 | 8020 | 9140 | 10250 | 10990 | 12350 | - | - |
| 25 | 5930 | 7040 | 8020 | 9140 | 10250 | 10990 | 12350 | - | - |
| 20 | 6350 | 7540 | 8600 | 9790 | 10980 | 11770 | 13220 | - | - |
| 15 | 6590 | 7830 | 8920 | 10150 | 11390 | 12210 | 13710 | - | - |
| 5 CYC. | 7230 | 8900 | 10470 | 12040 | 13710 | 14910 | 16850 | 17780 | 18520 |
| STATIC | 11080 | 13630 | 16050 | 18460 | 21020 | 22860 | 25850 | 27260 | 28390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.