

FLOTATION 648

TIRE SIZE	350/65 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	139 A8/135 B
LI/SS FREE ROLLING	151 A8/147 B



ABMESSUNGEN IS STANDARD

SW (MM)	358	RIM REC	AG 11.75
OD (MM)	1030	ECE	E11-106R-004551
SLR (MM)	451	PR	18
RC (MM)	3069		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.00	3.00	4.00	5.00
10 FR	2830	3585	4240	4830
20 FR	2545	3225	3820	4345
30 FR	2260	2865	3395	3865
40 FR	2020	2560	3030	3450
50 FR	1820	2305	2725	3075
10 DW	1990	2520	2990	3400
20 DW	1790	2270	2690	3060
30 DW	1590	2015	2390	2720
40 DW	1420	1800	2135	2430
50 DW	1280	1620	1920	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.