

## TR 135

|                  |                     |
|------------------|---------------------|
| <b>TIRE SIZE</b> | <b>13.6 - 24</b>    |
| <b>UM</b>        | US STANDARD         |
| <b>MACHINERY</b> | TRACTEUR / REMORQUE |
| <b>VERSION</b>   | STANDARD            |
| <b>TIRE TYPE</b> | TT                  |
| <b>LI/SS</b>     | 120 A8              |



### DIMENSIONS US STANDARD

|                 |          |                                      |                |
|-----------------|----------|--------------------------------------|----------------|
| <b>CODE USA</b> | 94003303 | <b>RIM ALT</b>                       | W 11           |
| <b>OD (IN)</b>  | 48.0     | <b>ECE</b>                           | E4-106R-002028 |
| <b>SLR (IN)</b> | 22.1     | <b>PR</b>                            | 8              |
| <b>RC (IN)</b>  | 145.6    | <b>TRA CODE</b>                      | R1             |
| <b>RIM REC</b>  | W 12     | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 44.73          |

### LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>28</b> |
|------------------|-----------|
| 25               | 3080      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.