

# ROCK STAR IND4

|                     |                                                                 |
|---------------------|-----------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>14.00 - 24</b>                                               |
| <b>UM</b>           | IS STANDARD                                                     |
| <b>CONSTRUCTION</b> | ❖ BIAS                                                          |
| <b>MACHINERY</b>    | CARRETILLA ELEVADORA /<br>MANIPULADOR DE CONTENEDORES<br>VACIOS |
| <b>VERSIÓN</b>      | PORT INDUSTRIAL                                                 |
| <b>TIRE TYPE</b>    | TL                                                              |



## DIMENSIONES IS STANDARD

|                 |          |                 |          |
|-----------------|----------|-----------------|----------|
| <b>OD (MM)</b>  | 1425     | <b>RIM ALT</b>  | 10.00 VA |
| <b>SLR (MM)</b> | 635      | <b>PR</b>       | 28       |
| <b>RC (MM)</b>  | 4350     | <b>TRA CODE</b> | IND4     |
| <b>RIM REC</b>  | 10.00 WA |                 |          |

## LOAD CAPACITY (KG/TIRE)

|                   |              |
|-------------------|--------------|
| <b>KM/H / BAR</b> | <b>10.00</b> |
| 10                | 13500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.