

# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>800/65 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	176 A8 ; 173 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	775	<b>RIM REC</b>	DW 27 B
<b>OD (MM)</b>	1820	<b>RIM ALT</b>	DH 27 B ; DW 25 B
<b>SLR (MM)</b>	823	<b>ECE</b>	E4-106R-001428
<b>RC (MM)</b>	5558	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.0	3.2	3.6
50	3175	3660	4485	4900	5385	5865	6350	6500	-	-
40	3450	3975	4875	5325	5850	6375	6900	7100	-	-
30	3695	4255	5220	5700	6260	6825	7385	7600	-	-
10 LT	4625	5330	6535	7140	7840	8545	9250	9515	-	-
10 HT	3695	4255	5220	5700	6260	6825	7385	7600	-	-
10 CYC.	-	5655	7230	7960	9250	10140	11055	11540	12025	12440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.