


AGRIMAX FORCE

IF 710/75 R 34

| | |
|---------------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 178 D |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94053643 | RC (IN) | 227.4 |
| SW (IN) | 28.2 | RIM REC | DW 25 B |
| OD (IN) | 75.9 | RIM ALT | DW 23 B |
| SLR (IN) | 34.3 | ECE | E11-106R-003017 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 7070 | 8120 | 9330 | 10530 | 11730 | 12930 | 14140 | 15050 |
| FROM 40 TO 25 | 7770 | 8930 | 10250 | 11570 | 12900 | 14220 | 15540 | 16500 |
| 20 | 8080 | 9280 | 10660 | 12040 | 13400 | 14780 | 16160 | 17200 |
| 12 | 8390 | 9630 | 11070 | 12500 | 13920 | 15350 | 16780 | 17860 |
| 5 | 9870 | 11330 | 13020 | 14690 | 16370 | 18050 | 19730 | 21000 |
| UPTO 20 CYC | 10100 | 11610 | 13330 | 15050 | 16770 | 18480 | 20200 | 21490 |
| UPTO 10 CYC | 12040 | 13830 | 15880 | 17930 | 19980 | 22030 | 24080 | 25630 |
| UPTO 5 CYC | 13200 | 15180 | 17430 | 19680 | 21920 | 24170 | 26420 | 28110 |
| 5 HT | 8080 | 9280 | 10660 | 12040 | 13400 | 14780 | 16160 | 17200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.