


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 126 A8 |
| LI/SS FREE ROLLING | 139 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94018758 | RC (IN) | 100.0 |
| SW (IN) | 11.4 | RIM REC | 9.00 |
| OD (IN) | 34.1 | ECE | E11-106R-003510 |
| SLR (IN) | 15.0 | PR | 14 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 70 |
|-----------|------|
| 5 FR | 7500 |
| 15 FR | 6370 |
| 20 FR | 6000 |
| 25 FR | 5360 |
| 5 DW | 5250 |
| 15 DW | 4460 |
| 20 DW | 4200 |
| 25 DW | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.