

# TR 145

|                     |                         |
|---------------------|-------------------------|
| <b>TIRE SIZE</b>    | 160/90 - 12             |
| <b>UM</b>           | IS STANDARD             |
| <b>CONSTRUCTION</b> | BIAS                    |
| <b>MACHINERY</b>    | SMALL TRACTOR / TRACTOR |
| <b>VERSION</b>      | STANDARD                |
| <b>TIRE TYPE</b>    | TT                      |
| <b>LI/SS</b>        | 76 A6                   |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 160  | <b>RIM REC</b>  | 4.00            |
| <b>OD (MM)</b>  | 631  | <b>ECE</b>      | E11-106R-005854 |
| <b>SLR (MM)</b> | 294  | <b>PR</b>       | 6               |
| <b>RC (MM)</b>  | 1969 | <b>TRA CODE</b> | R1              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.50</b> |
| 30                | 400         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.