


# AGRIMAX SPARGO SB

<b>TIRE SIZE</b>	<b>VF 270/95 R 48</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR / BESPRUTNINGSBIL
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94076499	<b>RC (IN)</b>	211.5
<b>SW (IN)</b>	11.0	<b>RIM REC</b>	W9
<b>OD (IN)</b>	68.7	<b>ECE</b>	E11-106R-0010463
<b>SLR (IN)</b>	32.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
45	3660	4140	4600	4990	5540	5850	6390	6940	7400	7790
FROM 40 TO 25	4030	4540	5050	5470	6080	6420	7020	7610	8130	8550
20	4110	4630	5150	5590	6200	6550	7160	7760	8290	8720
12	4180	4720	5250	5690	6320	6670	7290	7920	8450	8890
5	4430	5000	5560	6020	6680	7060	7720	8380	8940	9410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.