DATA SHEET

PRINTED ON
21-04-2026

AIROMAX AM 543

TIRE SIZE	**445/95 R 25**
UM	US STANDARD
CONSTRUCTION	
MACHINERY	MOBILE CRANE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	177 E

DIMENSIONS US STANDARD

USA CODE	94036660	**RIM REC**	11.25/2.0
OD (IN)	58.3	**RIM ALT**	11.00/1.7 CR; 11.00/1.7CRL
SLR (IN)	26.4		
RC (IN)	177.2		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	131
20	20900
25	19800
30	18700
35	18200
43	16100
50	13200
55	11400
62	9650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..