

# AT 603

<b>TIRE SIZE</b>	<b>12.5/80 -18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	IMPLEMENTOS AGRÍCOLAS / IMPLEMENTOS AGRÍCOLAS / RETROESCAVADORA / RETROESCAVADORA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	129 A8
<b>LI/SS FREE ROLLING</b>	142 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94019595	<b>RC (IN)</b>	119.2
<b>SW (IN)</b>	12.1	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	39.4	<b>RIM ALT</b>	11
<b>SLR (IN)</b>	17.6	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>54</b>
<b>5 FR</b>	8180
<b>15 FR</b>	6960
<b>20 FR</b>	6550
<b>25 FR</b>	5840
<b>5 DW</b>	5710
<b>15 DW</b>	4850
<b>20 DW</b>	4560
<b>25 DW</b>	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.