

# AGRIMAX RT 955

|                  |                                                          |
|------------------|----------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>270/95 R 48</b>                                       |
| <b>UM</b>        | IS STANDARD                                              |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>HARVESTER / IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                 |
| <b>TL/TT</b>     | TL                                                       |
| <b>LI/SS</b>     | 144 A8/B                                                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 275  | <b>RIM REC</b> | W 9            |
| <b>OD (MM)</b>  | 1733 | <b>RIM ALT</b> | W 8 ; W 10     |
| <b>SLR (MM)</b> | 820  | <b>ECE</b>     | E4-106R-000782 |
| <b>RC (MM)</b>  | 5351 | <b>SRI</b>     | 825            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|------|
| <b>50</b>  | 1095 | 1430 | 1740 | 1905 | 2020 | 2215 | 2410 | 2605 | 2800 | -    |
| <b>40</b>  | 1095 | 1430 | 1740 | 1905 | 2020 | 2215 | 2410 | 2605 | 2800 | -    |
| <b>30</b>  | 1170 | 1530 | 1860 | 2040 | 2160 | 2370 | 2580 | 2790 | 3000 | -    |
| <b>10</b>  | 1305 | 1640 | 2020 | 2395 | 2775 | 2860 | 3195 | 3530 | 3865 | 4200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.