


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 250/85 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 112 A8/B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94047666 | RC (IN) | 134.7 |
| SW (IN) | 9.9 | RIM REC | W 8 |
| OD (IN) | 44.8 | RIM ALT | W 7; W 9 |
| SLR (IN) | 20.4 | ECE | E4-106R-000646 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------|------|------|------|------|------|------|
| 30 | 1370 | 1590 | 1810 | 2030 | 2250 | 2470 |
| 25 | 1370 | 1590 | 1810 | 2030 | 2250 | 2470 |
| 20 | 1450 | 1700 | 1940 | 2170 | 2410 | 2650 |
| 5 LT | 1830 | 2130 | 2420 | 2720 | 3020 | 3320 |
| 5 HT | 1450 | 1700 | 1940 | 2170 | 2410 | 2650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.