


FL 635

TIRE SIZE	750/45 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HEUPRESSE / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D



ABMESSUNGEN US STANDARD

USA-CODE	94048786	RC (IN)	150.0
SW (IN)	29.7	RIM REC	AG 24.00
OD (IN)	49.1	ECE	E4-106R-002653
SLR (IN)	21.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3600	4110	4620	5740	6530	7540	8550	9340	10240	11240
40	3960	4520	5070	6300	7160	8280	9390	10250	11240	12350
30	4780	5460	6130	7630	8670	10020	11360	12410	13600	14950
25	5380	6140	6890	8580	9740	11260	12780	13940	15290	16800
20	5970	6810	7650	9510	10820	12500	14170	15490	16970	18650
15	6250	7130	8000	9950	11320	13070	14840	16200	17760	19510
5	7120	8120	9120	11340	12900	14890	16900	18450	20230	22220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.