


# POWERTRAILER SR 331

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>560/60 R 22.5</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SLÄPVAGN / ARBETSFORDON /<br>TANKBIL   |
| <b>VERSION</b>      | IMPLEMENT  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 165 D  |



## DIMENSIONER IS STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>OD (MM)</b>  | 1245     | <b>RIM ALT</b> | 17.00; AG18.00   |
| <b>SLR (MM)</b> | 565      | <b>ECE</b>     | E11-106R-0010087 |
| <b>RC (MM)</b>  | 3775     | <b>SRI</b>     | 600              |
| <b>RIM REC</b>  | AG 16.00 |                |                  |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.2  | 3.6  | 4    | 4.5  | 5    |
|------------|------|------|------|------|------|
| 10         | 6860 | 7505 | 8255 | 8810 | 9270 |
| 25         | 6020 | 6590 | 7245 | 7735 | 8135 |
| 40         | 5180 | 5670 | 6235 | 6655 | 7005 |
| 50         | 4610 | 5045 | 5550 | 5925 | 6230 |
| 65         | 3810 | 4170 | 4585 | 4895 | 5150 |
| 70         | 3465 | 3795 | 4170 | 4455 | 4685 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.