

EARTHMAX SR 43



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 43

EARTHMAX SR 43 (L-4) is an All Steel radial tyre specially designed for wheel loaders operating in severe rocky conditions, primarily underground mining. The tyre delivers excellent performance in load and carry operations in open pit mines, quarries and scrap yards. Its unique tread design offers superior traction and stability. Thanks to its All Steel casing, EARTHMAX SR 43 (L-4) provides excellent durability, resistance to snags and punctures as well as a long service life.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 R 25	TL	L4	***	221 A2	25.00/3.5	-	0	785	1875	847	5644	61	CR
	29.5 R 25	TL	L4	**	216 A2	25.00/3.5	-	0	785	1875	847	5644	61	CR
NEW	29.5 R 25	TL	E4/L4	****/***		25.00/3.5	-	-	785	1875	847	5644	61	CR
Ø29"	29.5 R 29	TL	L4	***	223 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	768	2003	905	6029	62	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES			
						
	E4/L4/SH4	A2				
		274 kg				

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	875/65 R 29 (35/65 R 29)	TL	L4	***	228 A2	27.00/3.5	27.00/3.0 28.00/3.5	0	852	1877	844	5702	61	CR
Ø33"	35/65 R 33	TL	L4	**	224 A2	28.00/3.5	-	0	900	2076	957	6412	61	CR
	35/65 R33	TL	E4/L4	****/***	-	28.00/3.5	-	0	900	2076	957	6412	61	CR
	35/65 R 33	TL	L4	***	229 A2	28.00/3.5	-	0	900	2076	957	6412	61	CR
	35/65 R33	TL	SH4	****	-	28.00/3.5	-	0	900	2076	957	6412	61	CR
Ø57"	60/80 R57	TL	L4	**	274 A2	47.00/5.0	47.00/6.0	0	1515	3930	1743	11840	90	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES			
						
	E4/L4/SH4					
						
A2	274 kg					

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026