

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	153 A8/149 B
<b>LI/SS FREE ROLLING</b>	165 A8/161 B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94006403	<b>RC (IN)</b>	137.8
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E4-106R-002306
<b>SLR (IN)</b>	20.1	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	38
<b>5 FR</b>	14420	15170	15890
<b>10 FR</b>	12970	13660	14310
<b>20 FR</b>	11530	12140	12720
<b>25 FR</b>	10300	10840	11350
<b>30 FR</b>	9270	9750	10200
<b>5 DW</b>	10220	10760	11260
<b>10 DW</b>	9190	9680	10140
<b>20 DW</b>	8170	8610	9020
<b>25 DW</b>	7300	7680	8050
<b>30 DW</b>	6570	6910	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.