


# AS 504

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	83 A8
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	164	<b>RIM REC</b>	4.00 E
<b>OD (MM)</b>	735	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (MM)</b>	343	<b>ECE</b>	E4-106R-002836
<b>RC (MM)</b>	2190	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80
10 FR	965
25 FR	820
30 FR	775
40 FR	690
10 DW	680
25 DW	575
30 DW	545
40 DW	485

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.