

AS 504

TIRE SIZE	11.5/80 - 15.3
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	290	RIM REC	9.00
OD (MM)	867	ECE	E11-106R-003510
SLR (MM)	380	PR	14
RC (MM)	2540	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.80
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430
10 DW	2380
25 DW	2025
30 DW	1905
40 DW	1700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.