

EARTHMAX SR 22



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 22

EARTHMAX SR 22 (G-2/L-2) is an All Steel radial tyre specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø24"	14.00 R 24	TL	G2/L2	*	153 A8 175 A2	8.00 TG	10.00 VA 9.00 GR	0	366	1370	625	4141	25	CR
Ø25"	23.5 R 25	TL	G2/L2	*	170 A8 195 A2	19.50/2.5	-	0	610	1614	709	4863	33,5	CR
	20.5 R 25	TL	G2/L2	*	161 A8 186 A2	17.00/2.0	17.00/1.7	0	525	1490	640	4315	32	CR
	20.5 R 25	TL	E2/L2	**	177 B 193 A2	17.00/2.0	17.00/1.7	0	525	1490	640	4315	32	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES			
						
						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 09/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
17.5 R 25	TL	G2/L2	*	153 A8 176 A2	14.00/1.5	-	0	452	1350	590	3950	28	CR
17.5 R 25	TL	E2/L2	**	167 B 182 A2	14.00/1.5	-	0	452	1350	590	3950	28	CR
15.5 R 25	TL	G2/L2	*	146 A8 169 A2	12.00/1.3	-	0	385	1275	557	3841	28	CR
23.5 R 25	TL	E2/L2	**	185 B 201 A2	19.50/2.5	-	0	610	1614	709	4863	33,5	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES			
						
						
B	201 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 09/09/2026