


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 D ; 181 AB



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94063420	<b>RC (IN)</b>	233.3
<b>SW (IN)</b>	27.8	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	77.1	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	34.7	<b>ECE</b>	E11-106R-006178

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
40	6450	7640	8760	9750	10910	11900	13060	14050	15380	16530
30	6780	7990	9200	10250	11460	12500	13720	14760	16150	17360
25	7100	8370	9640	10740	12000	13090	14370	15460	16920	18190
20	7420	8750	10090	11220	12550	13690	15020	16170	17690	19010
5 LT	8640	10200	11750	13070	14630	15960	17500	18840	20610	22160
5 HT	7420	8750	10090	11220	12550	13690	15020	16170	17690	19010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.