DATA SHEET

Última actualizac
2-06-2026

MAGLIFT

TIRE SIZE	**7.50 - 15**
UM	IS STANDARD
CONSTRUCTION	◆ SOLID
MACHINERY	CARRETILLA ELEVADORA
VERSIÓN	STANDARD

DIMENSIONES IS STANDARD

SW (MM)	193	**RIM REC**	6.0 - 15
OD (MM)	756		
SLR (MM)	0		
RC (MM)	0		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	-
25 LOAD WHEEL	3900
25 STEER WHEEL	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..