



IS standard



GROWING TOGETHER

# COMMANDER (F)



PRODUCT DATA SHEET



Bias



A6



Technologies



Deep Tread

Performance



Durability



High Load Capacity



Cut and Chip Resistance



# COMMANDER (F)

COMMANDER (F) is a front 3-rib pattern tire - perfect for soil tillage and haulage applications. Its deep tread made of a cut-and-chip resistant compound ensures a longer tire life, together with high load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	5.50 - 16	4.00 E	3.50 D ; 4.50 E	155	720	340	2145	STD	6	TT	86 A6
	6.00 - 16	4.50 E	4.00 E ; 5.00 F	175	750	357	2308	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	770	362	2332	STD	8	TT	98 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	770	362	2332	STD	10	TT	102 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	210	810	381	2477	STD	8	TT	103 A6

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference