

# LG RIB

|                     |                    |
|---------------------|--------------------|
| <b>TYRE SIZE</b>    | <b>16X6.50 - 8</b> |
| <b>UM</b>           | IS STANDARD        |
| <b>CONSTRUCTION</b> | ❖ BIAS             |
| <b>MACHINERY</b>    | TRACTOR            |
| <b>VERSION</b>      | ARAMID BELTED      |
| <b>TYRE TYPE</b>    | TL                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                              |
|-----------------|------|----------------|------------------------------|
| <b>SW (MM)</b>  | 170  | <b>RIM REC</b> | 5.375   - 55;   - 70;   - 90 |
| <b>OD (MM)</b>  | 408  | <b>ECE</b>     | E11-106R-005404              |
| <b>SLR (MM)</b> | 182  | <b>PR</b>      | 10                           |
| <b>RC (MM)</b>  | 1183 |                |                              |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.90</b> |
| 15                | 480         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.