

AW 705

| | |
|---------------------------|---|
| TIRE SIZE | 16.0/70 - 20 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 154 A8 |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------|
| USA-CODE | 94026227 | RC (IN) | 124.2 |
| SW (IN) | 16.1 | RIM REC | 13.0 |
| OD (IN) | 42.3 | RIM ALT | 12 SDC; 13 SDC; 14 |
| SLR (IN) | 18.9 | ECE | E11-106R-003368 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51 |
|-----------|-------|
| 5 FR | 11570 |
| 15 FR | 9840 |
| 20 FR | 9260 |
| 25 FR | 8270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.