

FLOTATION 558

TIRE SIZE	400/55 - 22.5
UM	US STANDARD
CONSTRUCTION	✠ BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / CISTERNA MÓVEL / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	138 A8/134 B
LI/SS FREE ROLLING	150 A8/146 B



DIMENSÕES US STANDARD

CÓDIGO USA	94006243	RC (IN)	121.4
SW (IN)	15.9	RIM REC	AG 11.75
OD (IN)	40.2	RIM ALT	12.25; 13.00; AG 13.00
SLR (IN)	17.5	ECE	E4-106R-002261

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	46	51
5 FR	9450	9810	10340
10 FR	8500	8830	9300
20 FR	7550	7850	8270
25 FR	6750	7010	7390
30 FR	6070	6300	6610
5 DW	6650	6910	7290
10 DW	5990	6220	6560
20 DW	5320	5530	5830
25 DW	4750	4940	5200
30 DW	4280	4440	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.