

AGRIMAX V-FLECTO

TYRE SIZE	VF 710/65 R 46 NRO
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	188 E



DIMENSIONS IS STANDARD

SW (MM)	735	ECE	E11-106R-0011961
OD (MM)	2090	SRI	975
SLR (MM)	943.5	TRA CODE	R1W
RC (MM)	6310	TREAD DEPTH (MM)	58
RIM REC	DW 25 B	TKPH (TK/H)	0
RIM ALT	DW 23 B ; MW 25 B		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2
70	2060	2365	2715	3065	3415	3765	4115	4375	9300	10000
FROM 65 TO 40	2060	2365	2715	3065	3415	3765	4115	4375	9300	10000
30	2095	2405	2765	3120	3475	3835	4190	4460	9490	10200
20	2135	2455	2820	3185	3545	3910	4275	4550	9675	10400
10	2260	2595	2980	3365	3750	4135	4520	4810	10230	11000
UPTO 10 CYC&NBSP;WITH FRONT LOADER	3050	3505	4025	4545	5065	5585	6105	6495	13815	14850
10HT	2095	2405	2765	3120	3475	3835	4190	4460	9490	10200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.