

# AGRIMAX FORCE

|                  |                                                          |
|------------------|----------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 800/70 R 38 CFO</b>                                |
| <b>UM</b>        | IS STANDARD                                              |
| <b>MACHINERY</b> | MOISSONNEUSE / TRACTEUR DE<br>FORTE PUISSANCE / TRACTEUR |
| <b>VERSION</b>   | STANDARD                                                 |
| <b>TIRE TYPE</b> | TL                                                       |
| <b>LI/SS</b>     | 184 D                                                    |

## DIMENSIONS IS STANDARD

|                 |      |                |                           |
|-----------------|------|----------------|---------------------------|
| <b>SW (MM)</b>  | 794  | <b>RIM REC</b> | DW 27 B                   |
| <b>OD (MM)</b>  | 2085 | <b>RIM ALT</b> | DW 25 B, DW 28 B, DW 30 B |
| <b>SLR (MM)</b> | 923  | <b>ECE</b>     | E11-106R-006497           |
| <b>RC (MM)</b>  | 6184 | <b>SRI</b>     | 975                       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0  | 1.2   | 1.4   | 1.6   | 2.0   | 2.4   |
|----------------------|------|------|------|-------|-------|-------|-------|-------|
| <b>70</b>            | 3845 | 4500 | 5155 | 5730  | 6305  | 6795  | 7615  | 8190  |
| <b>FROM 65 TO 40</b> | 4230 | 4950 | 5670 | 6300  | 6930  | 7470  | 8370  | 9000  |
| <b>30</b>            | 4395 | 5145 | 5895 | 6550  | 7205  | 7765  | 8700  | 9360  |
| <b>20</b>            | 4565 | 5345 | 6120 | 6800  | 7480  | 8065  | 9035  | 9720  |
| <b>10</b>            | 5370 | 6285 | 7200 | 8000  | 8800  | 9485  | 10625 | 11430 |
| <b>UPTO 30 CYC</b>   | 5495 | 6435 | 7370 | 8190  | 9005  | 9710  | 10880 | 11700 |
| <b>UPTO 15 CYC</b>   | 6555 | 7670 | 8785 | 9765  | 10740 | 11575 | 12970 | 13950 |
| <b>UPTO 10 CYC</b>   | 7190 | 8415 | 9635 | 10710 | 11780 | 12695 | 14225 | 15300 |
| <b>10 HT</b>         | 4395 | 5145 | 5895 | 6550  | 7205  | 7765  | 8700  | 9360  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

