DATA SHEET

Última atualização
2-06-2026

AGRIMAX TERIS

TIRE SIZE	**IF 710/75 R 32 CFO**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	CEIFEIRA / COLHEDORA DE ALGODÃO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	183 A8/B

DIMENSÕES IS STANDARD

SW (MM)	716	**RIM REC**	DW 25 B
OD (MM)	1879	**RIM ALT**	DW 23 B
SLR (MM)	851	**ECE**	E11-106R-005025
RC (MM)	5653	**SRI**	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3415	4025	4640	5775	6300	6915	7440	8140	8750
40	3415	4025	4640	5775	6300	6915	7440	8140	8750
30	3655	4310	4965	6185	6745	7400	7965	8710	9365
15 CYC*	5295	6240	7190	8955	9770	10720	11535	12620	13565
10 CYC*	6145	7245	8350	10395	11340	12445	13390	14650	15750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..