

# TF 8181

**5.00 - 16**

|                     |                                      |
|---------------------|--------------------------------------|
| <b>UM</b>           | IS STANDARD                          |
| <b>CONSTRUCTION</b> | BIAS                                 |
| <b>MACHINERY</b>    | TEK ÇEKER TRAKTÖR / TRAKTÖR / RÖMÖRK |
| <b>VERSION</b>      | SPECIAL                              |
| <b>TIRE TYPE</b>    | TT                                   |
|                     | 84 A6                                |



## UNDEFINED IS STANDARD

|                 |      |                |                   |
|-----------------|------|----------------|-------------------|
| <b>SW (MM)</b>  | 140  | <b>RIM REC</b> | 4.00 E            |
| <b>OD (MM)</b>  | 680  | <b>RIM ALT</b> | 3.00 D; 4 J; 4½ J |
| <b>SLR (MM)</b> | 322  | <b>ECE</b>     | E11-106R-004090   |
| <b>RC (MM)</b>  | 2025 | <b>PR</b>      | 6                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.20</b> |
| 30                | 500         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.