


# MULTIMAX MP 522



<b>TIRE SIZE</b>	<b>460/70 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 A8/B

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94031313	<b>RC (IN)</b>	148.3
<b>SW (IN)</b>	18.3	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	49.2	<b>RIM ALT</b>	DW 14 L; DW 16 L
<b>SLR (IN)</b>	22.4	<b>ECE</b>	E4-106R-002396

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	4630	5500	6270	7140	8010	8590	9650	-	-
25	4630	5500	6270	7140	8010	8590	9650	-	-
20	4960	5900	6720	7650	8580	9190	10330	-	-
15	5150	6120	6970	7940	8900	9550	10710	-	-
5 CYC	5650	6960	8180	9410	10710	11650	13170	13900	14470
STATIC	8660	10660	12540	14430	16420	17870	20190	21310	22190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.