

## SM 55 L5S

|                  |                                                                    |
|------------------|--------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>35/65 -33</b>                                                   |
| <b>UM</b>        | IS STANDARD                                                        |
| <b>MACHINERY</b> | VEHÍCULOS PARA MINERÍA<br>SUBTERRÁNEA / VOLQUETE DE PERFIL<br>BAJO |
| <b>VERSIÓN</b>   | ARASHIELD                                                          |
| <b>TIRE TYPE</b> | TL                                                                 |



### DIMENSIONES IS STANDARD

|                 |           |                 |     |
|-----------------|-----------|-----------------|-----|
| <b>OD (MM)</b>  | 2085      | <b>PR</b>       | 48  |
| <b>SLR (MM)</b> | 0         | <b>TRA CODE</b> | L5S |
| <b>RC (MM)</b>  | 0         |                 |     |
| <b>RIM REC</b>  | 28.00/3.5 |                 |     |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.25</b> |
| 10                | 29000       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.