

# MULTIMAX MP 515

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 425/75 R 20 MPT                                                                          |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ<br>/ ТЕХНИКА ДЛЯ ВНЕСЕНИЯ<br>УДОБРЕНИЙ                          |
| VERSION      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 148 G                                                                                    |



## РАЗМЕРЫ IS STANDARD

|          |      |         |                                |
|----------|------|---------|--------------------------------|
| SW (MM)  | 421  | RIM REC | 13                             |
| OD (MM)  | 1146 | RIM ALT | 13 SDC; 11 SDC; 12 SDC; 11; 12 |
| SLR (MM) | 522  | ECE     | E11-54R-0017872                |
| RC (MM)  | 3491 |         |                                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.5  | 3.0  | 3.5  | 4.0  |
|------------|------|------|------|------|------|------|
| 90         | 1540 | 1810 | 2150 | 2490 | 2820 | 3150 |
| 65         | 1675 | 1965 | 2335 | 2705 | 3060 | 3420 |
| 40         | 1775 | 2085 | 2475 | 2865 | 3245 | 3625 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.