


RIDEMAX IT 697 (M+S)



| | |
|---------------------|--|
| TIRE SIZE | 650/65 R 42 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 171 D ; 176 A8 |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 645 | RIM REC | DW 20 B |
| OD (MM) | 1920 | RIM ALT | DW 18 L |
| SLR (MM) | 880 | ECE | E4-106R-002659 |
| RC (MM) | 5869 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 2890 | 3565 | 4180 | 4860 | 5475 | 6150 |
| 50 | 3125 | 3855 | 4520 | 5250 | 5915 | 6645 |
| 40 | 3335 | 4120 | 4830 | 5610 | 6320 | 7100 |
| 30 | 3470 | 4280 | 5020 | 5830 | 6570 | 7380 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.