


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>375/70 R 20 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VÉHICULE UNIVERSEL / CAMION D'ENGRAIS / VÉHICULE UNIVERSEL
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	136 G



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	377	<b>RIM REC</b>	12
<b>OD (MM)</b>	1034	<b>RIM ALT</b>	W 10; DW 10; 11; 11 SDC; W 11; DW 11; 12 SDC
<b>SLR (MM)</b>	472	<b>ECE</b>	E11-54R-0016139
<b>RC (MM)</b>	3121		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.5	3.0	3.5
90	1210	1435	1705	1975	2240
65	1315	1560	1855	2145	2435
40	1395	1655	1965	2275	2580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.