


# AGRIMAX FORCE

<b>TYRE SIZE</b>	<b>IF 710/55 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94059904	<b>RC (IN)</b>	181.7
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	60.8	<b>ECE</b>	E11-106R-005716
<b>SLR (IN)</b>	27.0	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4880	5620	6470	7220	8070	8810	9880	10630
<b>FROM 40 TO 25</b>	5370	6180	7120	7940	8870	9690	10860	11700
20	5580	6430	7400	8240	9230	10070	11290	12150
12	5790	6670	7680	8560	9580	10460	11720	12610
5	6810	7850	9040	10070	11260	12300	13780	14840
<b>UPTO 20 CYC</b>	6980	8040	9250	10320	11530	12590	14110	15190
<b>UPTO 10 CYC</b>	8310	9580	11030	12300	13750	15010	16820	18110
<b>UPTO 5 CYC</b>	9120	10500	12100	13490	15080	16470	18450	19860
5 HT	5580	6430	7400	8240	9230	10070	11290	12150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.